

## VECTOR TWO (formerly IHUB 4 Building)

## Building Specifications NORTHGATE CYBERZONE September 15, 2008



1. Location : Ihub 4, Northgate CyberZone, Filinvest Corporate City

Alabang Zapote Road, Alabang, Muntinlupa City

Building Size/Stories : 19,646.72 sq.m. Gross Floor Area ; 14 storeys

3. Parking per Building: Podium Parking : 170 slots

4. Typical Floor Plate : Single Tenancy

Gross Leasable Area = (inclusive of Limited Common Areas)

Ground Floor : 1,701.61 sq.m 5<sup>th</sup> Floor : 1,581.36 sq.m. Typical Floor : 1,581.36 sq.m. Usable Area = (exclusive of General and Limited Common Area)

Ground Floor 1,385.83 sq.m 5<sup>th</sup> Floor 1,352.80 sq.m. Typical Floor

1,352.80 sq.m

Floor Efficiency using GLA

Ground Floor 81 % 5<sup>th</sup> Floor 86 % Typical Floor 86%

Note: Areas are approximates only and may have some discrepancy on

actual site.

5. Turnover Condition: Bare Shell, rough flooring, fire sprinkler and smoke detectors for

installation., Fan Coil Units provided

6. Telecomm. Facilities: Under ground fiber optic cabling facilities with dark fiber provisions

> for all telcos' expansion. Current Telcos' providing services are PLDT, Globe, Eastern Communications, Bayantel, Cablelink and Digitel

7. Electricity Specification: 3 MVA transformer for each building

Service Voltage 460V, 3P, 60Hz

8. Back-up Generators:

Emergency Power Supply: 100% power back-up

No. of generator available: TWO

Capacity and coverage : 1,400 KVA each Location of the generator: Podium Level 4

Downtime between normal power to back-up power during power

failure; 10 second (estimate)

Back-up time : Operation thru fuel (14,000 liters);

approximately 36hourscontinuous running.

**UPS** : It is recommended that tenant install its

own UPS.

9. Floor Loading : Live Load : 75 PSF

10. Air-Conditioning System : Type of air-con system : Chilled Water Type 1,200 TR capacity

> (4 Chiller at 300 TR). A Fifth chiller (300TR) serves as standby. Additional 198 can be pick up from the building AHU that serves as make

up pre-cooling unit.

1 ton per 18 sq.m. of leas able area Air con capacity

> 77.5 tons – ground floor 77.5 tons – typical floor

Ducting & additional FCUs: To be provided by tenants. FCUs to

be of the same brand installed

: P 195.00/Sq.m./ month 24 x 7 usage Air-con charges

12. Power Loading Maximum of 150 volt amperes per square meter (includes lighting and

air-con load)

13. Ceiling Height Slab to slab : 4.50 m (Ground Floor)

: 4.00 m (Typical Floors)

Slab to lowest beam : 3.05 m (Typical Floors) **14. Elevators** : Three (3) elevators

Speed: 150 meters per minute

Brand: Fuji

Capacity: 1,500 kg = 25 persons (est.)

**15. Loading Area** : Exterior

**16. Fire Protection** : Automatic Sprinkler System

**Smoke Detectors** 

Fire Alarm (manual pull and annunciator)

Wet and Dry stand pipes Fire hose cabinets 2 floor

Fire Extinguishers : Two per floor at common area;

Tenant to provide in its space as per Fire Department requirement

Exit doors : Two per floor @ 1,600 mm and 1,000 mm = 2,600 mm total exit per

floor

Staircase : Two per floor @ 2,000 mm + 1,600 mm/floor = 3,600 mm flight width;

350 persons maximum allowable loading occupancy

**18. Lightning Protection:** Protected by high mast air terminal

**19. Security** : CCTV on common areas only

It is recommended for tenants to provide their own Security Monitoring

System

**20. Water Supply :** Source : Deepwell

Supply : FCC Water System

**21. Garbage Disposal** : Garbage for pick-up; there is a trash storage room

23. Building Management:

Automation

Monitoring of all plumbing & fire protection equipment, Air

Conditioning System (transfer Pumps), Ventilation System, Security

System, Elevators status, Normal & Emergency Power System

**24. Facilities / Amenities :** Restroom facilities per floor

Men's = 4 cubicles (including disabled), 5 urinals, & 4 lavatories

Ladies' = 6 cubicles (including disabled), 6 water closets & 5 lavatories Provisions/stub outs for executive toilets provided within tenants'

space (4 stub outs in 4 locations)

Slop sink at the janitors' closet in the toilet rooms.

Convergence Block : FastBytes (Indoor and Al Fresco dining center)

**Basketball Court** 

Cable TV Provider : Cablelink

**25. Utilities** : Tenants are individually metered. Tenant to provide sub-meter for

power and water

**26. Other Fees/Bond/Insurance**: Building Management Fee: P65.00/sq.m./month

Air Con Charges P195.00/sq.m./month 24 x 7 usage.

Power/Electricity deposit: P460,000.00 per floor subject to adjustment based on the LESSEE's actual 1 month average consumption over a 6 months period

Construction Monitoring/: P65.00 per rentable square meter or

Plan Evaluation Fee

Construction Bond :P300,000.00 + P100.00 per rentable square

meter refundable after fit our period.

Insurance :Lessee shall secure a comprehensive

general liability insurance coverage: combined single liability of not less than P2,000,000.00 for any bodily injuries or property damage to third parties for the

duration of the fit-out period.

I. Developer : CyberZone Properties, Inc.

## II. Consultants/Contractors

1. Conceptual Architects : Studios Architecture (California)

2. Local Architects : R. Villarosa Architects

3. Structural Designer : Aromin & Sy

4. Electrical Consultant : Iraido T. Legaspi & Associates.
5. Mechanical Consultant : LRPunzalan & Associates
6. Sanitary/ Plumbing/Fire Protection: Mendoza Engineering
7. Project Manager : AMCON & Company, Inc..

**8. General Contractor** : JDBEC Inc.

**9. Elevator Contractor** : General Elevator (Brand Fuji)

**10.Generator Supplier** : Multico

